

## LUXLIFT LIGHT SERIES

Smart lifting system for lighting, advertising and displays

LUXLIFT	LL-12	LL-25	LL-35	LL-50
Lifting weight	up to 12 kg	up to 25 kg	up to 35 kg	up to 50 kg
Power Motor	30 W	60 W	90 W	120 W
Lowering distance	0 - 20 m			
Load suspension rope	twist-proof 2-point load suspension, high-tech fiber material			
Operation mode	via App on tablet, or wired			
Power connection	Separate power supply for light and motor			
Additional contacts	for DALI, DMX, emergency power etc.			
Operating counter	for light, monitoring of lamp lifespan			
Current draw standby	0.08 A			
Load plate	with safety lock, relief, and protection of the suspension rope			
Power supply Motor	100-264 V / 50-60 Hz			
Power supply Light	100-264 V / 50-60 Hz			
Current Light Circuit	max. 10 A			
Cable Light Circuit	3 x 1.0 mm <sup>2</sup>			
Cable auxiliary contacts	4 x 0.75 mm <sup>2</sup>			
Current auxiliary contacts	max. 6 A			
Protection category	IP54			
Protection class	I			
Temperature range	-15 °C to +60 °C			
Net weight	6.3 kg			6.9 kg
Speed	approx. 3 - 3.5 m/min			
Sound pressure level	< 60 dB			
Dimensions	230 x 230 x 230 mm			



All Luxlifts have the following functions built in and can be easily configured using the Luxlift -App:

- Up to 9999 individual lifts can be controlled
- Up to 99 groups and synchronous groups
- Up to 50 lifts per group
- Synchronous groups with up to 4 lifts
- 2 storable lowering distances

Luxlift HandelsgmbH reserves the right to make changes to the technical data without prior notice. Luxlift HandelsgmbH assumes no liability for typesetting and printing errors. No claims can be derived from the information in this data sheet.